



# EZY-TURN® #22

## GATE VALVE SEAT SEALANT & BODY FILLER LUBRICANT

### DESCRIPTION

**EZY-TURN® #22** is a premium sealant formulated from a unique blend of synthetic and vegetable-based oils for use in expanding gate type valves. The ideal sealant for service applications involving gases, distillates, dilute acids, and steam. **EZY-TURN #22** contains no solid fillers that could disrupt the sealing film. Although designed for expanding gate-type valves, **EZY-TURN #22** is used effectively on many other valve types.

- Nontoxic
- Nonhazardous
- No Solid Fillers
- Reduces Torque
- Seals, Lubricates
- Vegetable & Synthetic Base
- Water resistant
- Multi-Purpose
- Hydrocarbon Resistant
- Pumpable

### APPLICATIONS

**Oilfield:** **EZY-TURN #22** has been formulated for use in production oilfield situations (Christmas trees, line valves) where a variety of service conditions may be required. This is a premium product and should be used where solid fillers mandated in the “peanut butter” type sealants are not wanted. **Industrial and Marine:** **EZY-TURN #22** is also recommended for gate valve applications requiring resistance to hydrocarbon or hydrocarbon/water mixtures. Absence of solid fillers assures that the service will not be contaminated with unwanted solids.

### SERVICE RECOMMENDATIONS

- Petroleum Gases
- Petroleum Liquids
- Natural Gas
- Crude Distillates
- Dilute Alkalis
- Aqueous Solutions
- Butane
- Propane
- LPG
- Crude Oil
- Dilute Acids
- Salt Solutions

### PRODUCT CHARACTERISTICS

|  |                                    |
|--|------------------------------------|
| <b>Appearance</b>  |                                    |
| Bulk & Stick   | Amber Sticky Paste or Semi-Plastic |
| <b>Penetration (ASTM D-217)</b>                          |                                    |
| Bulk   | 255 – 285                          |
| Stick  | 80 - 130                           |
| <b>Density (lb/gal), Typical</b>                         |                                    |
| Bulk   | 8.72                               |
| Stick  | 8.94                               |
| <b>Specific Gravity, Typical</b>                         |                                    |
| Bulk   | 1.04                               |
| Stick  | 1.07                               |
| <b>Dropping Point (ASTM D-2265)</b>                      |                                    |
| Bulk & Stick   | None                               |
| <b>Oil Separation (FTMS 791.B M.321.2) (ASTM D-6184)</b> |                                    |
| Bulk   | 5.0 max                            |
| Stick  | 1.0 max                            |
| <b>Thickener</b>   |                                    |
| Bulk & Stick   | Inorganic                          |
| <b>Temperature Range</b>                                 |                                    |
| Bulk & Stick   | -50°F (-46°C) to 420°F (215°C)     |

**Note:** Not for use with oxygen or strong oxidizers.

**For package types and part numbers contact [sales@jetlube.com](mailto:sales@jetlube.com).**

### LIMITED WARRANTY

For warranty information please visit [http://www.jetlube.com/pdf/Jet-Lube\\_Warranty.pdf](http://www.jetlube.com/pdf/Jet-Lube_Warranty.pdf)

You can also email us at [sales@jetlube.com](mailto:sales@jetlube.com) or write to the Sales Department at the address below.