

### DESCRIPTION

**EZY-PAK™ #120** is a general-purpose graphite packing compound recommended for hydrocarbon and aqueous services. It is an injectable packing material that can be pumped into internal voids in valves and other equipment with a high-pressure lubricator. Under pressure, **EZY-PAK #120** will conform to the shape of any void and form a gasket or seal.

**EZY-PAK #120** is formulated with hydrocarbon resistant vegetable oils, polymers, Graphite & other inert fillers and high temperature fibers blended to produce a dough-like packing compound. It is best pumped through an injection valve with a 1/8" or larger bore, but can also be pumped (with more effort) through giant button head fittings.

- Vegetable Oil Base
- Color: Grey/Black
- Water Resistant
- Nonhardening
- Nontoxic
- Pumpable
- Nonhazardous
- Economical

### APPLICATIONS

**EZY-PAK #120** can be used in any application in which an injectable packing is desired to fill an internal void. It is hydrocarbon and water resistant and provides excellent sealing capacity when injected under pressure into valve bonnets, stuffing boxes, and other areas requiring packing.

### SERVICE RECOMMENDATIONS

- Crude Oil
- LPG Systems
- Aqueous Solutions
- Steam
- Kerosene
- Liquid & Gas Aliphatic Hydrocarbons
- Propane
- Brine
- Water
- Gasoline
- Natural Gas
- Crude Distillates

### TEMPERATURE RANGE

-0°F (-18°C) to 750°F (400°C)

### PRODUCT CHARACTERISTICS

|                                       |                         |
|---------------------------------------|-------------------------|
| Appearance                            | Grey/Black Fibrous Mass |
| Penetration<br>(ASTM D-2596)          | 40 – 90                 |
| Density (lb/gal) Typical              | 12.1                    |
| Specific Gravity                      | 1.45                    |
| Dropping Point<br>(ASTM D-2265)       | None                    |
| Oil Separation Wt. %<br>(ASTM D-6184) | 1.0 max.                |
| Thickener                             | Polymeric & Inorganic   |
| Flash Point<br>(ASTM D-92)            | > 400°F (204°C)         |
| pH Range                              | 0 – 14                  |

**Note: Not for use with oxygen or strong oxidizers.**

**For package types and part numbers contact [sales@jetlube.com](mailto:sales@jetlube.com).**

### LIMITED WARRANTY

For warranty information please visit [http://www.jetlube.com/pdf/Jet-Lube\\_Warranty.pdf](http://www.jetlube.com/pdf/Jet-Lube_Warranty.pdf)

You can also email us at [sales@jetlube.com](mailto:sales@jetlube.com) or write to the Sales Department at the address below.