

DESCRIPTION

EZY-PAK #125 packing compound is specifically designed for use in severe arctic conditions. Formulated from synthetic binders, silicone based polymers, inert fillers and fibers, **EZY-PAK #125** will conform to any shape, preventing leaks and/or foreign materials from entering the valve cavity. Excellent water resistance allows use for steam applications.

- Nontoxic
- Color: Light Blue
- Nonhardening
- Synthetic Base
- Nonhazardous
- Water Resistant
- Pumpable
- Hydrocarbon Resistant

APPLICATIONS

EZY-PAK #125 is specifically designed to provide a flexible packing for applications such as oilfield valve and wellhead used in arctic conditions. Due to the synthetic base, **EZY-PAK #125** is particularly effective in hot water, brine, and aqueous solutions or steam services to 550°F (288°C).

EZY-PAK #125 can be injected into any area requiring packing with a high-pressure lubricator. It is best pumped through an injection valve having a 1/8" or larger bore, but can be pumped through a giant button head fitting with more effort.

SERVICE RECOMMENDATIONS

- Liquid Hydrocarbons
- Gaseous Hydrocarbons
- Aqueous Solutions
- Crude Distillates
- Crude Oil
- Brine
- Water
- Steam

TEMPERATURE RANGE

-75°F (-60°C) to 750°F (400°C)

PRODUCT CHARACTERISTICS

Appearance	Light blue, semi-plastic, fibrous mass
Penetration (ASTM D-217)	45 – 75
Density (lb/gal) Typical	12.6
Specific Gravity	1.5
Dropping Point (ASTM D-2265)	None
Oil Separation Wt. % (ASTM D-6184)	1.0 max.
Thickener	Polymers & Mineral Silicates
Flash Point (ASTM D-92)	> 500°F (260°C)

Note: Not for use with oxygen or strong oxidizers.

For package types and part numbers contact sales@jetlube.com

LIMITED WARRANTY

For warranty information please visit http://www.jetlube.com/pdf/Jet-Lube_Warranty.pdf

You can also email us at sales@jetlube.com or write to the Sales Department at the address below.