



MARINE-MOLY™

MOLYBDENUM DISULFIDE PASTE

DESCRIPTION

MARINE-MOLY™ is a specially formulated Molybdenum Disulfide (MoS₂) and graphite marine lubricating paste that provides a low-friction shield by “plating” to metal surfaces to reduce bearing temperature, protect working parts, prevent galling and heat freeze. Very tenacious, it may be applied by brush or spatula to hot surfaces without running or dripping off.

MARINE-MOLY is extremely resistant to water, withstands extreme weather elements and helps prevent corrosion on metal exposed to water, steam, salt spray, etc. **MARINE-MOLY** has a 300,000 psi film strength.

- Lead Free
- Service rating: -300°F (-185°C) to 750°F (400°C)
- Water Resistant
- Non-melting
- Contains Moly
- Color - Black
- Available in convenient aerosol package

APPLICATIONS

- Highly Opened Gears
- Loading Racks & Arms
- Marine Transmission Gears
- Open Spur Gears
- Sliding Bases

PRODUCT CHARACTERISTICS

Color	Black
Penetration (ASTM D-217)	275 – 305
Density (lb/gal)	8.76
Specific Gravity	1.05
Flash Point (ASTM D-92)	> 550°F (288°C)
Shell 4-Ball (ASTM D-2596)	
Weld Point, kg	315
Load Wear Index	66.21
Wear Scar (ASTM D-2266)	0.617
Dropping Point (ASTM D-566)	None
Thickener Type	Clay
Base Oil Type	ISO 460 Petroleum
Copper Strip Corrosion (ASTM D-4048)	1B
Water Spray Off Resistance (ASTM D-4049)	<40%

For package types and part numbers contact sales@jetlube.com.

LIMITED WARRANTY

For warranty information please visit http://www.jetlube.com/pdf/Jet-Lube_Warranty.pdf

You can also email us at sales@jetlube.com or write to the Sales Department at the address below.