



RUBBER LUBRICANT™

WATER-BASED MOLD RELEASE AGENT

DESCRIPTION

JET-LUBE's Water-Based RUBBER LUBRICANT and MOLD RELEASE AGENT is a multipurpose, environmentally safe silicone product that provides excellent performance. Contains twice the silicone content of leading aerosols for increased protection.

When used as a RUBBER LUBRICANT, it makes assembly of plastic and rubber parts fast and easy. Whether squirted, sprayed, or brushed on, RUBBER LUBRICANT provides a temporary, wet, slippery surface, and then either dries to a thin protective film, or is absorbed into natural or synthetic rubber.

As a MOLD RELEASE AGENT, the larger silicone content and higher silicone viscosity provides maximum release capacity under even the most severe molding conditions. Excellent for all metal, plastic, and rubber castings. Heat stable to 500°F. Nonflammable. Will not melt or gum.

- Nontoxic
- Odorless
- Tasteless
- Nonstaining
- Ozone Friendly
- Low Foaming
- Heat Stable
- Environmentally Safe
- Nonflammable

APPLICATIONS

RUBBER LUBRICANT

- Boots
- Bumpers
- Channels
- Diaphragms
- "O" Rings
- Glass Setting
- Shock Mountings
- Vibration Mountings
- Wiring Harnesses
- Wheels & Tires

MOLD RELEASE

Formulated for acrylics, celluloses, ABS resins, polystyrenes, rubber, melamines and metal.

For best results, apply immediately before assembling, cutting, etc.

PRODUCT CHARACTERISTICS

Appearance	Ivory to White Fluid
Density (lb/gal), typical	8.3
Specific Gravity	1.0
Base Silicone Viscosity (ASTM D-445)	2000 cSt @ 25°C
Emulsion Viscosity	3 cSt @ 40°C
Dilution Stability	Excellent
Storage Stability	Good

For package types and part numbers contact sales@jetlube.com.

LIMITED WARRANTY

For warranty information please visit

http://www.jetlube.com/pdf/Jet-Lube_Warranty.pdf

You can also email us at sales@jetlube.com or write to the Sales Department at the address below.